

ND 25 de-humidifier



25 Ltrs / Day
extraction capacity



Recommended Upto 2500-3000 cu.ft
indicative coverage area



Premium Brand From Singapore
since 2003 in india



Digital Display
to view / set humidity & temperature



Semi Permanent Built In Ionizer
for fresh indoor air quality



Auto Restart
resumes operation once power comes on



Auto Resume
pre-set humidity levels maintained on power resumption



ND 25

Specifications

Extraction (30°C, 80% RH)	l/day	25
Recommended Coverage (Indicative) (Domestic)	cu.ft.	3500-4000
Recommended Coverage (Indicative) (Industry)	cu.ft.	2500-3000
Power consumption, Power supply 220V-240V/50Hz	watt	300
Air Flow		200 m ³ /hr 117 cfm
Noise Level (Approx.)	db	40
Dimensions (W X D X H)	inches	14" x 8" x 23"
Tank Capacity	l	5
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-134a
Empty Weight	kg	14.3
Running Temperature		5°C – 35°C
Switch Off Timer		Yes
Air Purification		Carbon Filter
Ionizer	kg	Inbuilt Ionizer
Auto Restart Auto Resume		Available Available
Programmable On Off Timer		Optional



Negative Ion Density+: + Negative ion density measurement is based from source emission. Up to 20 Million/cm³

Industries



Home



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum & Art Galleries



Defense