

ND 50 de-humidifier



50 Ltrs / Day
extraction capacity



Recommended Upto 5,000 to 6,000 cu. ft.
indicative coverage area



Premium Brand From Singapore
since 2003 in india



Digital Display
to view / set humidity & temperature



Pre-filter Screen and Carbon Filter
to remove harmful pollutants and germs, and keep air fresh



Silent Mode
makes very less noise



High Air Flow @ 630 m³/hr
for efficient and seamless performance



ND 50

Specifications

Extraction (30°C, 80% RH)	l/day	50
Recommended Coverage (Indicative) (Home)	cu.ft.	upto 6,000
Recommended Coverage (Indicative) (Industry)	cu.ft.	upto 5,000
Power consumption, Power supply 220V-240V/50Hz	watt	530 watts Rated Power 620 watts Max. Power
Air Flow Maximum		630 m3/hr 373 cfm
Air Flow Minimum		450 m3/hr 266 cfm
Noise Level (Approx.)	db	60 dB Max. 50 dB Min.
Dimensions (W X D X H)	inches	15 x 11 x 26
Tank Capacity	l	5
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-410a
Empty Weight	kg	20.2
Running Temperature		5°C – 35°C
Programmable Timer		Yes



Industries



Home



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense