

de-humidifier

ND 838



30 Ltrs / Day
extraction capacity



Recommended Upto 3000-3500 cu.ft
indicative coverage area



Premium Brand From Singapore
since 2003 in india



Digital Display
to view / set humidity & temperature



Semi Permanent Built In Ionizer
for fresh indoor air quality



Auto Restart
resumes operation once power comes on



Auto Resume
pre-set humidity levels maintained on power resumption



ND838

Specifications

Extraction (30°C, 80% RH)	l/day	30	
Recommended Coverage (Indicative) (Home)	cu.ft.	4000	113 cu.mt.
Recommended Coverage (Indicative) (Industry)	cu.ft.	3000	84 cu.mt.
Power consumption, Power supply 220V-240V/50Hz	watt	405	
Negative Ion Density*		Up to 20 Million/cm ³	
Air Flow	m ³ / hr	250	
Noise Level (Approx.)	db	46	
Dimensions (W X D X H)	inches	16" x 11" x 25"	
Tank Capacity	l	6	
Humidity Setting		Electronic	
Compressor		Rotary	
Refrigerant		R-410a	
Empty Weight	kg	15.8	
Running Temperature		5°C – 35°C	
Programmable Timer		Yes	

Negative Ion Density + Negative ion density measurement is based from source emission. ≥ 20 Million/cm³



Certifications



RoHS

Industries



Home



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense