

O53p built to perform



53 Ltrs / day
extraction capacity



Recommended upto 5000 cu.ft
indicative coverage area



Anti-corrosive Body
roto molded housing for robust handling



Led Display and Electronic Control
precise operation



Water Pump
dispenses condensate up to 15ft



Higher Air Flow @ 420 m³/hr
for consistent and low levels of RH



O53p

Specifications

| | | |
|---|-----------------|-------------------------------------|
| Extraction (l/24hr) (30°C, 80% RH) | l/24 hr | 53 |
| Recommended Coverage (Indicative)(Industry) | cu.ft. cu.mt. | Upto 5000 Upto 142 |
| Power consumption, Voltage 220V-240V/50Hz | watts | 635 |
| Air Flow | | 420 m ³ / hr 247 cfm |
| Noise Level (Approx.) | db | 55 |
| Dimensions (W X D X H) | inches | 20" x 17" x 28" |
| Tank Capacity | | Condensate drainage with water pump |
| Humidity Setting | | Electronic |
| Compressor | | Rotary |
| Refrigerant | | R-410a |
| Empty Weight | kg | 33.5 |
| Running Temperature | | 5°C – 35°C |
| Auto Restart Auto Resume | | Available |
| Switch Off Timer | | No |
| Programmable On Off Timer | | Optional |



Ductable Option
air outlet can be ducted for focused drying



Big Wheels and Big Metal Handle
to ensure optimum on-site mobility



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense